

CETAC ASX 520 Random Access Intelligent Autosampler

# ASX • 520

#### ACCURATE

Never Misses a Cup: Precision engineered automated sample probe arm and stationary sample racks virtually eliminate errors.

Auto Zero Feature: Intelligent sample probe re-homing device dramatically reduces accidental sample intake errors

Integrated Rinse Station: Continuous flow sample probe rinse station with peristaltic pump minimizes sample contamination and carryover.

## **Technical Specifications**

Height:	25 cm (9.8")	Tray:	4 rack capacity
	61 cm (24")	Racks:	90 x 7 ml
with sample probe			60 x 14 ml
			40 x 20 ml
Width:	52 cm (20.5")		24 x 30 ml
			21 x 50 ml
Depth:	48.2 cm (19")		
Weight: 10.5 kg (23 lbs)			



**Corrosion Resistant:** Sealed electronics chassis and coated metal parts protect against the harshest chemical environments.

Superior Material Construction: PTFE and PEEK used to construct a metal-free liquid flow path.

Motor Torque: Robust X, Y, Z axis movement decreases effects of environmental buildup.

#### SIMPLE

Easy Set-Up and Operation: Out-of-the-box set-up allows a fully operational system the day of delivery.

**Internet Accessible Firmware:** Downloadable firmware from the internet simplifies the reprogramming process.

#### ADAPTABLE

**Portable:** Compact design with over 60 interfaces with host instruments from 20 manufacturers enable multiple applications in a single lab.

Flexible Rack Configuration: Five different rack sizes from 90 x 7 ml to 21 x 50 ml. Compatible with other standard market, ready-made sample racks. Customized racks made to customer specifications.

### RELIABLE

**Precision Engineered:** Unrivaled accuracy combined with extreme durability is the benchmark for CETAC Automation.

Computer/Hardware Interfaces: 5 auxiliary outputs and 5 inputs, RS232, USB, direct control and IEEE-488 option.

Power Requirements: 100 - 240 VAC +/- 10%, 50/60 Hz

Model Number: ASX - 520 Autosampler

Optional Accessories: Clean Enclosure (ENC-500) Extended Rack (EXR-8) Autodilutor (ADX-500) Septum Piercing

Warranty: 1 year limited.

Ordering: To discuss your specific needs, please contact your CETAC representative.

> CETAC Technologies 14306 Industrial Rd. Omaha, NE 68144 USA Tel. 402.733.2829 Fax.402.733.5292 www.cetac.com

Sample Solutions for Tomorrow's Lab